



Boss XL3™ Hydroxyl Generator

Product Specifications



* air mover not included

Boss XL3™ Hydroxyl Generator

The Boss XL3™ hydroxyl generator is designed for larger areas that require strong hydroxyl output to sanitize and deodorize. It can be used in large commercial open spaces and is ideal to treat large surfaces affected by fire and smoke, flood, nicotine, grey/black water, decomposition, mold, sewage and chemical spills or off-gassing. This unit is designed for use with an existing air mover (air mover is not included).

The table below summarizes the minimum treatment area in the absence of ventilation, and the treatment area range under typical operating conditions: 3 air changes per hour, 90% recirculated air, and 9 foot (2.7 m) ceilings. If the treated space contains a high contaminate or odor load, the effective treatment area will be smaller than the range listed below. These guidelines should be adhered to for optimal performance and safety.

Operating Guidelines

Minimum Area (if there is no air circulation)	2,000 ft ² [186 m ²]
Treatment Range (ft²)	1,700 - 3,250
Treatment Range (m²)	158 - 302

Specifications

Dimensions (LxWxD): 11.12" x 20.25" x 20.25" (283mm x 514mm x 514mm)

Weight: 25lbs, 11.4kg

Voltage: 120V @ 60Hz / 230V @ 50Hz

Power: 195 Watts (max) Without Blower

Number of Optics: 3

Shipping Dimensions: 22.0" x 15.0" x 29.5" (559mm x 381mm x 749mm)

Shipping Weight: 30lbs, 13.6kg

Certification: ETL US/Canada, CE, RoHS, REACH

Warranty: 2 years covering defects in workmanship or materials, but excluding

spare parts and consumables

Distributed by:

Bio-Shine, Inc. / OdoroxAir 190 Summerhill Road Spotswood, NJ 08884 T: 732-251-9506 E: odoroxair@bio-shine.com www.odoroxair.com